

## SAKRAL STRAIGHT CUT ROUNDED CORNER

- Eye-catching peak and trough structure
- Robust appearance thanks to the impressive thickness of its material
- If requested, the surface can be roughened to aid the rapid development of a natural patina
- Especially suitable for old church roofs, castles and palaces
- Natural, timeless and dignified beauty
- Configure roofs to suit your needs, thanks to the wide range of cut shapes

### TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Size (appr.)                        | 180 x 380 x 18 mm      |
| Max. coverage width (approx.)       | 180 mm                 |
| Min. gauge (approx.)                | 145 mm                 |
| Covering length on av. approx.      | 155 mm                 |
| Max. gauge (approx.)                | 165 mm                 |
| Average tile requirement (approx.)  | 36 pcs/m <sup>2</sup>  |
| Unit weight (approx.)               | 2.6 kg/piece           |
| Weight per m <sup>2</sup> (approx.) | 93.6 kg/m <sup>2</sup> |
| Weight per pallet (approx.)         | 1141 kg                |
| Pcs per mini-pack                   | 6 piece                |
| Pcs per pallet                      | 360 piece              |



APPLICATIONS

| ADDITIONAL MEASURES ACCORDING TO CREATON MANUFACTURER'S SPECIFICATIONS   |        |
|--|--------|
| Standard roof pitch CREATON DE in combination with additional measures according to manufacturer's specifications<br>Standard roof pitch CREATON DE in combination with additional measures according to manufacturer's specifications | 24 °   |
| Installation of a trussing sheet/glued sub-roof without nail seals, possible CREATON products: DUO extra, DUO longlife ND extra, TRIO extra, QUATTRO longlife extra  | ≥ 24 ° |
| Installation of a trussing sheet/glued sub-roof without nail seals, possible CREATON products: DUO longlife ND extra   | ≥ 22 ° |
| Installation of a trussing sheet/glued sub-roof with nail seals, possible CREATON products: DUO extra, DUO longlife ND extra, TRIO extra, QUATTRO longlife extra   | ≥ 22 ° |
| Installation as a rainproof sub-roof, possible CREATON products: DUO longlife ND extra, TRIO extra, QUATTRO longlife extra   | ≥ 18 ° |
| Installation as a watertight sub-roof, possible CREATON products: QUATTRO longlife extra   | ≥ 10 ° |
| Installation as a watertight sub-roof welded in a 7° special solution, please observe separate installation guidelines, possible CREATON products: QUATTRO longlife extra  | -      |

TECHNICAL INFORMATIONS

- Please consider the sample letter for the standard CREATON roof pitches.

